

	Portable Version	USB Version	Rechargeable Version
Technical Information	0601	0601U	0602
Product			
Color	Silver / White	Silver / White	Silver Blue / White
Material	ABS	ABS	ABS
Rotation Type	High / Low	High / Low	High / Low
Button	Touch Control	Touch Control	Touch Control
Handle Material	ABS	ABS	ABS
Input			
Voltage	12.0VDC	6.0VDC	14.0VDC
Power	5W	5W	5W
Battery Type	8C Alkaline	4C Alkaline	8C Alkaline
Battery Life (8hours/day)	Low Speed : 100 hours High Speed : 90 hours	Low Speed : 30 hours High Speed : 20 hours	Low Speed : 100 hours High Speed : 90 hours
USB Cable	N/A	Available	N/A
Rechargeable Battery Type	N/A	N/A	Lithium Polymer
Rechargeable Battery Life	N/A	N/A	Low Speed : 9 hours High Speed : 5 hours
System			
Timer	2 / 4 hours	2 / 4 hours	2 / 4 hours
Adjustable Tilt Angle	15° Left and Right 15° Up and Down	15° Left and Right 15° Up and Down	15° Left and Right 15° Up and Down
Output			
Air Velocity (m³/min)	2.3 - 2.6 (High) / 1.0 - 1.1 (Low)	1.7 - 2.2 (High) / 1.1 - 1.6 (Low)	2.0 - 2.4 (High) / 1.4 - 1.6 (Low)
Air Flow Rate (m/s)	2.5 - 2.8 (High) / 1.0 - 1.1 (Low)	1.8 - 2.1 (High) / 1.2 - 1.5 (Low)	2.1 - 2.6 (High) / 1.5 - 1.8 (Low)
Rotation Speed (RPM)	≤ 1,650 (High) / ≤ 860 (Low)	≤ 1,870 (High) / ≤ 1,365 (Low)	≤ 1,890 (High) / ≤ 1,380 (Low)
Sound Level (dB)	≤ 65	≤ 65	≤ 65
Specifications			
Dimensions (W x D x H)	244 x 102 x 394mm	244 x 102 x 394mm	244 x 102 x 394mm
Weight	1.03 kg	1.06 kg	1.10 kg
Individual Box (W x D x H)	247 x 107 x 402mm	247 x 107 x 402mm	247 x 107 x 402mm
User Manual	A4, 2pages	A4, 2pages	A4, 2pages
Others			
Compliance	RoHS, CE, WEEE	RoHS, CE, WEEE	RoHS, CE, WEEE
Shipping Information			
Master Carton			
Dimensions (W x D x H)	514 x 341 x 432mm	514 x 341 x 432mm	514 x 341 x 432mm
Net Weight	7.60 kg	7.80 kg	8.10 kg
Gross Weight	8.50 kg	8.70 kg	9.00 kg
Units	6	6	6
Container			
20" Container	2,310 units	2,310 units	2,310 units
40" Container	4,830 units	4,830 units	4,830 units
Others			
HS Code	8414 5199	8414 5199	8414 5199

